

# FEATHERLITE

## FULL LINE CATALOG



# HOW TO SELECT A LADDER

## A GUIDE

### 1

#### Select a Type



##### STEP LADDER

The most popular style of ladder. Used from medium to low heights. Utilize pail shelves and tops to hold tools for the job.

##### SPECIALTY LADDER

Multi purpose ladder for use in many scenarios, as a step or extension ladder on multiple surfaces.

##### EXTENSION LADDER

The most versatile style of ladder, found in a variety of sizes. Most commonly used for higher elevations.

### 2

#### Select a Height

STEP LADDERS		
LADDER SIZE	APPROX. HIGHEST STANDING LEVEL	MAXIMUM REACH <sup>^</sup>
4'	1' 11"	8' 6"
5'	2' 10"	9' 5"
6'	3' 10"	10' 5"
7'	4' 9"	11' 4"
8'	5' 8"	12' 3"
10'	7' 7"	14' 2"
12'	9' 6"	16' 1"

EXTENSION LADDERS				
LADDER SIZE	MAXIMUM EXTENDED LENGTH	MAX. REACH <sup>^</sup>	WORKING RANGE TO TOP SUPPORT*	MAXIMUM ACCESSIBLE ROOF HEIGHT RANGE*
16'	13'	15' 11"	7 1/2' - 12 1/2'	4 1/2'-9 1/2'
20'	17'	19' 10"	9 1/2' - 16 1/2'	6 1/2'-13 1/2'
24'	21'	23' 8"	11 1/2' - 20'	8 1/2'-17"
28'	25'	27' 7"	13 1/2' - 24'	10 1/2'-21'
32'	29'	31' 5"	15 1/2' - 28'	12 1/2'-25'
36'	32'	34' 4"	17 1/2' - 31'	14'-28'
40'	35'	37' 3"	19' - 33 1/2'	16'-30 1/2'
44'	39'	41' 1"	21' - 37 1/2'	18'-34 1/2'

<sup>^</sup> Assumes 5' 7" person with 12" vertical reach

\*When set up at the proper 75 1/2° angle

### 3

#### Select a Load Capacity



**TYPE IAA:** Professional use. Super Heavy Duty. Capable of supporting 375 lbs.  
**USES:** MRO and industrial construction.




**TYPE IA:** Professional use. Extra Heavy Duty. Capable of supporting 300 lbs.  
**USES:** Roofing, building maintenance, contracting and industrial construction.



**TYPE I:** Industrial use. Heavy Duty. Capable of supporting 250 lbs.  
**USES:** Building maintenance, general contracting and sheet rock.



**TYPE II:** Commercial use. Medium Duty. Capable of supporting 225 lbs.  
**USES:** Light commercial and general repair, painting and cleaning.



**TYPE III:** Household use. Light Duty. Capable of supporting 200 lbs.  
**USES:** Light cleaning and painting.

### 4

#### Select a Ladder Material



##### ALUMINUM

- Lightweight
- Long-lasting construction
- Resists corrosion
- Ideal for painting, roofing and siding



##### FIBERGLASS

- Non-conductive when clean and dry
- Strong and durable
- Weather-resistant
- Great for heavy-duty construction

**AT FEATHERLITE A LOUISVILLE LADDER BRAND**, all of our products are designed and constructed to meet or exceed applicable standards and requirements of Canadian Standards Association (CSA), and the American National Standards Institute (ANSI). Please read the information on this page before using our products. Your safety is important to us.

## HOW TO SAFELY USE OUR LADDERS

Louisville Ladder Corp. manufacturers products in compliance with the applicable **CANADIAN NATIONAL STANDARDS (CSA)** and American National Standards Institute (ANSI), safety codes.

CSA is a developer of safety standards and a provider of product testing and certification services for portable ladders. The CSA certification mark  indicates the ladder has been tested and certified in conformity with the Z11-18 Portable Ladder standard. Certification is an ongoing process that involves follow up factory inspections and testing. Ladders displaying the CSA Certification mark provides our customers increased assurance of product quality and safety.

ANSI is a developer of safety standards for a wide variety of consumer and industrial products. Listed below are the individual ANSI ladder standards based on material or type of climbing product.

SCAFFOLDS, PLANKS AND STAGES: **ANSI A10.8**

WOOD LADDERS: **ANSI A14.1**

ACCESSORIES: **ANSI A14.8**

METAL LADDERS: **ANSI A14.2**

FIBERGLASS LADDERS: **ANSI A14.5**

STEEL LADDERS: **ANSI A14.7**

ATTIC LADDERS: **ANSI A14.9**

Both CSA and ANSI have established a Duty Rating which identifies the use for which a portable ladder is intended and the conditions under which the ladder can be used safely. An extensive series of tests and design requirements determines which Duty Rating label a ladder may receive. The total load supported includes the combined weight of the user, clothing, tools and any materials on the ladder. However, ladders must be used properly to support the intended load. See section "Select a Load Capacity" on previous page for more information on CSA and ANSI Duty Ratings.



**ANSI**

Meets or exceeds requirements  
of American National Standards Institute

**SAFETY IS EVERYONE'S RESPONSIBILITY.** Even a rigidly constructed ladder can be involved in an accident if the proper cautions are not taken in its use. Critical factors in safe use include reading all instructions and labels accompanying the ladder.



**DANGER:** Metal ladders conduct electricity and where contact may be made with live electrical circuits. Failure to read and follow instructions on the use of this product could result in serious personal injury or death.

### PROPER SELECTION

Select ladder of proper duty rating to support combined weight of user and materials. Ladders are available with duty ratings of 200, 225, 250, 300 and 375 lbs. Select ladder of proper length to safely reach desired height.

### INSPECTION BEFORE EACH USE

- Inspect thoroughly for missing or damaged components. Never use a damaged ladder and never make temporary repairs.
- Inspect thoroughly for loose fasteners. Make sure all working parts are in good working order (lubricate if necessary).
- Clean ladder of all foreign material (wet paint, mud, snow, grease, oil, etc.).
- Destroy ladder if damaged, worn, or exposed to fire or chemicals

### CONSIDER BEFORE EACH USE

- Metal ladders conduct electricity. Keep away from electrical circuits.
- Consult manufacturer for use in chemical or other corrosive environments.
- Use ladder only as outlined in instructions. Ladders are designed for one person only unless otherwise noted (i.e. twin front ladders). Do not overload.
- Do not use in high winds or during storm
- Do not use if in poor health, if taking any drugs or alcoholic beverages, or if physically handicapped
- Keep shoes clean. Leather soles should not be worn.
- Never leave ladder set up and unattended
- Pay close attention to what you are doing

### STEP LADDERS – PROPER SETUP AND USE

- Use help in setting up ladder, if possible
- Make sure ladder is fully open and spreaders locked
- Set all feet on firm, level surface. Do not place on unstable, loose or slippery surfaces. Place ladder where access is not obstructed. Do not place in front of unlocked doors. Ladders are not intended to be used on scaffolds.
- Secure ladder, where possible, from excessive movement

- Make sure spreaders are locked and ladder is stable before climbing
- Climb only front side of ladder. Face ladder when climbing up or down. Maintain a firm grip. Use both hands in climbing.
- Keep body centered between side rails. Do not overreach. Get down and move ladder as needed.
- Do not climb, stand, or sit above second step from top. Do not climb, stand, or sit on spreader braces, ladder top, or pail shelf.
- Do not straddle front and back. Do not climb from one ladder onto another.
- Avoid pushing or pulling off to side of ladder. Do not "walk" or "shift" ladder while on it.

For additional information see ANSI A14.1-Wood; A14.2-Aluminum; A14.5-Fiberglass. Twin front (mechanic) ladders and extension trestle ladders may be climbed from either side.

### SINGLE & EXTENSION LADDERS – PROPER SETUP AND USE

- Use help in setting up ladder, if possible
- Set base of ladder on firm, level surface. Ladder leveling devices are available for use on uneven ground. Place ladder where access is not obstructed.
- Do not place on unstable, loose, or slippery surfaces. Do not place in front of unlocked doors. Ladders are not intended to be used on scaffolds.
- Secure base section before raising ladder to upright position. Do not raise or lower with fly section extended.
- Extend fly section and engage runglocks. Make sure rope does not create a tripping hazard or interfere with activity near ladder.
- Recommend tying bottom fly rung to adjacent base rung
- Extend and retract fly section only from ground and when no one is on ladder.
- Do not overextend. A minimum overlap of sections is required as follows:
  - ladder size up to and including 32'-3" overlap
  - over 32' up to and including 36'-4" overlap
  - over 36' up to and including 48'-5" overlap
  - sizes over 48'-6" overlap

- Position ladder against upper support surface. Make sure ladder does not lean to side. Ladder must make a 75 1/2° angle with the ground.
- To establish if ladder is at proper angle – Determine the distance along the rail between the top and bottom support points of the ladder. Divide this distance by 4. The result will be the horizontal distance between the top and bottom support points.

- When using ladder for access to roof, extend top 3 feet above roof edge. Tie or secure top from movement.
- Make sure top and bottom ends of ladder are firmly supported
- Check that top and bottom of ladder are properly supported. Make sure runglocks are engaged before climbing.
- Face ladder when climbing up or down. Maintain a firm grip.
- Use both hands in climbing
- Keep body centered between side rails. Do not overreach. Get down and move ladder as needed.
- Do not climb above top support point. Do not climb from one ladder to another.
- Do not straddle or sit on rungs
- Avoid pushing or pulling off to side of ladder. Do not "walk" or "shift" ladder while on it.

### PROPER CARE AND STORAGE

- Hang ladder on racks at intervals of 6' for support
- Never store materials on ladder
- Never drop or apply an impact load to ladder
- Securely support ladder in transit
- Never paint a wood ladder. Treat with wood preservative.
- Protect wood ladder from exposure to the elements, but allow good ventilation. Keep away from heat and moisture.

## FIBERGLASS STEP

- 01 6800-AA • 375
- 6600-AA • 375
- 6400 • 300
- 02 6600 • 300
- 6900 • 300
- 6300 • 250
- 03 5800 • 225

## FIBERGLASS PLATFORM

- 03 6500-AA • 375
- 6500 • 300

## FIBERGLASS STRAIGHT

- 04 6100 • 375
- 5600D • 375
- 5300 • 375

## FIBERGLASS EXTENSION

- 05 9200D • 375
- 6200 • 375
- 6200D • 375
- 6900 • 300

## ALUMINUM STEP

- 06 3400 • 300
- 2400 • 225
- 3700 • N/A

## ALUMINUM STRAIGHT

- 07 4100 • 300
- 3100D • 300

## ALUMINUM EXTENSION

- 08 4200D • 300
- 3200D • 300
- 2200 • 225

## SPECIALTY

- 09 2700 • 300
- FXS6900 • 300

## CONNECT

- 10

## LOCATIONS

- 11

# FIBERGLASS STEP



Wrap Around Rail



Heavy Duty Gusset



Heavy Duty Boot



MODEL	LADDER SIZE	OPEN HEIGHT	HIGHEST STANDING LEVEL	BASE WIDTH	BASE DEPTH	APPROX.	MAX.
						WEIGHT LBS	REACH
6804-AA	4'	46 1/8"	1' 11"	20 15/16"	30 7/8"	16.8	8' 6"
6806-AA	6'	68 1/8"	3' 10"	23 15/16"	43 9/16"	24.0	10' 5"
6808-AA	8'	91 3/4"	5' 8"	26 15/16"	56 1/4"	32.0	12' 3"
6810-AA	10'	114 5/8"	7' 7"	29 15/16"	68 15/16"	44.2	14' 2"
6812-AA	12'	136 5/8"	9' 6"	32 15/16"	81 5/8"	54.2	16' 1"



TWIN STEP LADDER



MetalTop



Wrap Around Rail



Heavy Duty Boot



MODEL	LADDER SIZE	OPEN HEIGHT	HIGHEST STANDING LEVEL	BASE WIDTH	BASE DEPTH	APPROX.	MAX.
						WEIGHT LBS	REACH
6604-AA	4'	46 5/16"	1' 11"	22 1/4"	37 7/8"	22.1	8' 6"
6606-AA	6'	69 1/8"	3' 10"	25 1/4"	52 3/4"	30.4	10' 5"
6608-AA	8'	91 15/16"	5' 8"	28 1/4"	67 1/2"	40.6	12' 3"
6610-AA	10'	113 3/4"	7' 7"	31 1/4"	82 3/8"	58.7	14' 2"
6612-AA	12'	137 5/8"	9' 6"	34 1/4"	97 1/4"	72.6	16' 1"



Top with Tool Slots



Wrap Around Rail



Heavy Duty Boot



MODEL	LADDER SIZE	OPEN HEIGHT	HIGHEST STANDING LEVEL	BASE WIDTH	BASE DEPTH	APPROX.	MAX.
						WEIGHT LBS	REACH
*6402	2'	22 13/16"	1' 10"	18"	18 1/8"	10	8' 5"
6404	4'	45 5/8"	1' 11"	20 1/4"	29"	14	8' 6"
6406	6'	68 1/2"	3' 10"	23 3/8"	40"	21	10' 5"
6408	8'	91 5/16"	5' 8"	26 5/8"	53"	28	12' 3"
6410	10'	114 1/8"	7' 7"	29 5/8"	65 1/2"	40	14' 2"
6412	12'	136 15/16"	9' 6"	32 5/8"	76 15/18"	50	16' 1"

\*6402 is a step stool



ASSEMBLED IN  
ASSEMBLE AU  
CANADA

# FIBERGLASS STEP



TWIN STEP  
LADDER



Aluminum Top



Wrap Around Rail



Heavy  
Duty Boot



MODEL	LADDER SIZE	OPEN HEIGHT	HIGHEST STANDING LEVEL	BASE WIDTH	BASE DEPTH	APPROX. WEIGHT LBS	MAX. REACH
6603	3'	34 7/8"	1' 0"	19 1/4"	30 7/17"	16.8	7' 7"
6604	4'	46 5/16"	1' 11"	22 1/4"	37 7/8"	18.5	8' 6"
6606	6'	69 1/8"	3' 10"	25 1/4"	52 11/16"	27.9	10' 5"
6608	8'	91 15/16"	5' 8"	28 1/4"	67 1/2"	37.0	12' 3"
6610	10'	114 3/4"	7' 7"	31 1/4"	82 3/8"	46.4	14' 2"

ProTop™



Inside  
Spreader Brace



Heavy  
Duty Boot



MODEL	LADDER SIZE	OPEN HEIGHT	HIGHEST STANDING LEVEL	BASE WIDTH	BASE DEPTH	APPROX. WEIGHT LBS	MAX. REACH
6904	4'	45 5/8"	1' 11"	20 1/4"	29 7/8"	15.0	8' 6"
6906	6'	68 1/2"	3' 10"	23 3/8"	41 4/5"	20.8	10' 5"
6908	8'	91 5/16"	5' 8"	26 5/8"	53 4/9"	27.8	12' 3"
6910	10'	114 1/8"	7' 7"	29 5/8"	65 1/3"	38.3	14' 2"
6912	12'	136 15/16"	9' 6"	32 5/8"	77 1/8"	47.8	16' 1"

MoldedTop



Slip Resistant  
Tread



Raptor Boot™  
and SHOX™



MODEL	LADDER SIZE	OPEN HEIGHT	HIGHEST STANDING LEVEL	BASE WIDTH	BASE DEPTH	APPROX. WEIGHT LBS	MAX. REACH
6304	4'	45 9/16"	1' 11"	18 3/4"	28 5/8"	11.9	8' 6"
6305	5'	57"	2' 10"	20 3/16"	34 9/16"	14.0	9' 5"
6306	6'	68 3/8"	3' 10"	21 13/16"	40 7/16"	16.7	10' 5"
6308	8'	91 3/16"	5' 8"	24 13/16"	52 5/16"	22.2	12' 3"

# FIBERGLASS STEP



MODEL	LADDER SIZE	OPEN HEIGHT	HIGHEST STANDING LEVEL	BASE WIDTH	BASE DEPTH	APPROX. WEIGHT LBS	MAX. REACH
5804	4'	45 5/8"	1' 11"	18 7/8"	28"	12.7	8' 6"
5805	5'	57"	2' 10"	20 1/2"	33 1/2"	15.0	9' 5"
5806	6'	68 1/2"	3' 10"	22"	39 3/4"	17.4	10' 5"

MoldedTop



Pail Shelf



Raptor Boot™  
and SHOX™



Wide Platform  
14 5/16" x 18 1/16"



Wrap Around Rail



Heavy Duty Boot



MODEL	LADDER SIZE	OPEN HEIGHT	HIGHEST STANDING LEVEL	BASE WIDTH	BASE DEPTH	APPROX. WEIGHT LBS	MAX. REACH
6504-AA	4'	45 3/6"	1' 11"	23 7/8"	30 5/8"	15.8	8' 6"
6505-AA	5'	56 9/16"	2' 10"	24 3/8"	36 15/16"	20.2	9' 5"
6506-AA	6'	68"	3' 10"	26 7/8"	43 5/16"	24.9	10' 5"
6508-AA	8'	90 13/16"	5' 8"	29 7/8"	55 15/16"	32.0	12' 1"
6510-AA	10'	113 5/8"	7' 7"	32 7/8"	68 5/8"	44.3	14' 2"
6512-AA	12'	136 1/2"	9' 6"	35 3/4"	81 5/16"	53.3	16'

Wide Platform  
14 5/16" x 18 1/16"



Wrap Around Rail



Heavy Duty Boot



MODEL	LADDER SIZE	OPEN HEIGHT	HIGHEST STANDING LEVEL	BASE WIDTH	BASE DEPTH	APPROX. WEIGHT LBS	MAX. REACH
6504	4'	45 3/6"	1' 11"	23 7/8"	30 5/8"	15.8	8' 6"
6505	5'	56 9/16"	2' 10"	24 3/8"	36 15/16"	21.7	9' 3"
6506	6'	68"	3' 10"	26 7/8"	43 5/16"	24.9	10' 5"
6508	8'	90 13/16"	5' 8"	29 7/8"	55 15/16"	31.7	12' 3"
6510	10'	113 5/8"	7' 7"	32 7/8"	68 5/8"	44.6	14' 2"
6512	12'	136 1/2"	9' 6"	35 3/4"	81 5/16"	53.3	16' 1"

# FIBERGLASS PLATFORM



ASSEMBLED IN  
ASSEMBLÉ AU  
CANADA

# FIBERGLASS STRAIGHT



## Non-Marring End Caps



## Riveted Rung to Rail



## 1 Piece Foot Assembly



MODEL	LADDER SIZE	OUTSIDE WIDTH	INSIDE WIDTH	APPROX. WEIGHT (LBS)	MAX. REACH
6108	8'	16 11/16"	14 5/16"	19.9	11' 1"
6110	10'	16 11/16"	14 5/16"	23.8	13'
6112	12'	16 11/16"	14 5/16"	27.8	15'
6114	14'	16 11/16"	14 5/16"	31.5	16' 11"
6116	16'	16 11/16"	14 5/16"	35.1	18' 10"



## Non-Marring End Caps



## Riveted Rung to Rail



## Heavy Duty Foot




MODEL	LADDER SIZE	OUTSIDE WIDTH	INSIDE WIDTH	APPROX. WEIGHT (LBS)	MAX. REACH
5608D	8'	16 11/16"	14 5/16"	18.7	11' 1"
5610D	10'	16 11/16"	14 5/16"	22.9	13'
5612D	12'	16 11/16"	14 5/16"	26.6	15' 0"
5614D	14'	16 11/16"	14 5/16"	30.3	16' 11"
5616D	16'	16 11/16"	14 5/16"	34.9	18' 10"



## Narrow Inside width



## Rail Protector



## Slip Resistant Shoe



MODEL	LADDER SIZE	OUTSIDE WIDTH	INSIDE WIDTH	APPROX. WEIGHT (LBS)	MAX. REACH
5308	8'	12	9 5/8"	18.0	11' 1"
5310	10'	12	9 5/8"	21.6	13'
5312	12'	12	9 5/8"	26.7	15'
5314	14'	12	9 5/8"	28.6	16' 11"
5316*	16'	12	9 5/8"	34.5	18' 10"

# FIBERGLASS EXTENSION



Riveted Rung to Rail



Heavy Duty Foot



Raise From Rear



MODEL	LADDER SIZE	BASE SECTION			FLY SECTION			APPROX. WEIGHT LBS	MAX. REACH
		MAX. OPEN LENGTH	OUTSIDE WIDTH	INSIDE WIDTH	OUTSIDE WIDTH	INSIDE WIDTH			
9200D	16'	13'	16 11/16"	14 5/16"	15 11/16"	13 5/16"	40.4	15' 11"	
9220D	20'	17'	16 11/16"	14 5/16"	15 11/16"	13 5/16"	48.2	19' 10"	
9224D	24'	21'	16 11/16"	14 5/16"	15 11/16"	13 5/16"	56.0	23' 8"	
9228D	28'	25'	16 11/16"	14 5/16"	15 11/16"	13 5/16"	64.1	27' 7"	
9232D	32'	29'	16 11/16"	14 5/16"	15 11/16"	13 5/16"	71.8	31' 5"	
*9236D	36'	32'	17 3/8"	15"	16 1/16"	13 11/16"	87.0	34' 4"	
*9240D	40'	35'	17 3/8"	15"	16 1/16"	13 11/16"	98.0	37' 3"	

\*Grade IA orange fiberglass



Riveted Rung to Rail



Raise from Front



1 Piece Foot Assembly




MODEL	LADDER SIZE	BASE SECTION			FLY SECTION			APPROX. WEIGHT LBS	MAX. REACH
		MAX. OPEN LENGTH	OUTSIDE WIDTH	INSIDE WIDTH	OUTSIDE WIDTH	INSIDE WIDTH			
6200 / 6200D	16'	13'	16 11/16"	14 5/16"	15 11/16"	13 5/16"	42.0	16' 2"	
6220	20'	17'	16 11/16"	14 5/16"	15 11/16"	13 5/16"	49.1	20' 1"	
6224	24'	21'	16 11/16"	14 5/16"	15 11/16"	13 5/16"	56.6	23' 11"	
6228	28'	25'	16 11/16"	14 5/16"	15 11/16"	13 5/16"	64.4	27' 10"	
6232	32'	29'	16 11/16"	14 5/16"	15 11/16"	13 5/16"	71.8	31' 8"	
6216D	16'	13'	16 11/16"	14 5/16"	15 11/16"	13 5/16"	43.2	16' 2"	
6220D	20'	17'	16 11/16"	14 5/16"	15 11/16"	13 5/16"	50.2	20' 1"	
6224D	24'	21'	16 11/16"	14 5/16"	15 11/16"	13 5/16"	58.2	23' 11"	
6228D	28'	25'	16 11/16"	14 5/16"	15 11/16"	13 5/16"	66.1	27' 10"	
6232D	32'	29'	16 11/16"	14 5/16"	15 11/16"	13 5/16"	73.6	31' 8"	




MAX LOCK™

THE  
STRONGEST,  
TOUGHEST,  
LIGHTEST  
RUNG LOCK  
EVER.

D Rung



Max Lock



Swivel Foot



MODEL	LADDER SIZE	BASE SECTION			FLY SECTION			APPROX. WEIGHT LBS	MAX. REACH
		MAX. OPEN LENGTH	OUTSIDE WIDTH	INSIDE WIDTH	OUTSIDE WIDTH	INSIDE WIDTH			
6900	16'	13'	17 1/16"	14 11/16"	16 1/16"	13 11/16"	35.1	15' 11"	
6920	20'	17'	17 1/16"	14 11/16"	16 1/16"	13 11/16"	43.0	19' 10"	
6924	24'	21'	17 1/16"	14 11/16"	16 1/16"	13 11/16"	50.1	23' 8"	
6928	28'	25'	17 1/16"	14 11/16"	16 1/16"	13 11/16"	58.5	27' 7"	
6932	32'	29'	17 11/16"	15 5/16"	16 11/16"	14 5/16"	69.7	31' 5"	



ASSEMBLED IN CANADA

# ALUMINUM STEP



ProTop™



Pail Shelf



Heavy Duty Boot



MODEL	LADDER SIZE	OPEN HEIGHT	HIGHEST STANDING LEVEL	BASE WIDTH	BASE DEPTH	APPROX. WEIGHT LBS	MAX. REACH
*3402	2'	22 13/16"	22 13/16"	16 7/16"	17 1/4"	7.4	8' 5"
3404	4'	45 3/4"	22 13/16"	18 1/2"	30"	13.0	8' 6"
3406	6'	68 1/2"	45 5/8"	21 9/16"	42 3/4"	18.6	10' 5"
3408	8'	91 5/16"	68 1/2"	24 9/16"	55 1/2"	24.7	12' 3"
3410	10'	114 1/8"	91 5/16"	27 9/16"	68 1/4"	31.8	14' 2"
3412	12'	136 15/16"	114 1/8"	31 7/8"	77 3/4"	37.8	16' 1"

\*3402 is a step stool.



Top with Tool Slots



Pail Shelf



Slip Resistant Shoe



MODEL	LADDER SIZE	OPEN HEIGHT	HIGHEST STANDING LEVEL	BASE WIDTH	BASE DEPTH	APPROX. WEIGHT LBS	MAX. REACH
2404	4'	45 15/16"	23"	17 3/4"	27 13/16"	9.6	8' 6"
2406	6'	68 3/4"	46"	20 3/4"	41 1/8"	13.0	10' 5"
2408	8'	91 5/8"	68"	23 5/16"	51 5/8"	18.4	12' 3"
2410	10'	114 7/16"	91"	26 1/16"	64 1/4"	24.2	14' 2"




Wide Design



Slip Resistnat Shoe



Combine Sizes to Create a Plank



MODEL	SIZE	OPEN HEIGHT	BASE WIDTH	BASE DEPTH	APPROX. WEIGHT LBS	MAX. REACH
3702	2'	22 1/8"	33 3/16"	24 5/8"	11.7	N/A
3703	3'	33 3/8"	33 7/8"	32 3/4"	16.5	N/A
3704	4'	44 3/4"	34 9/16"	40 3/4"	21.7	N/A

# ALUMINUM STRAIGHT



## Box Section Design



## Aluminum Round Rung



## Swivel Shoe



MODEL	LADDER SIZE	OUTSIDE WIDTH	INSIDE WIDTH	APPROX. WEIGHT (LBS)	MAX. REACH
4108	8'	14 5/8"	12 7/8"	13.3	11' 1"
4110	10'	14 5/8"	12 7/8"	16.3	13' 0"
4112	12'	14 5/8"	12 7/8"	19.4	15' 0"
4114	14'	14 5/8"	12 7/8"	22.4	16' 11"
4116	16'	15 7/8"	13 7/8"	30.3	18' 10"
4118	18'	15 7/8"	13 7/8"	33.3	20' 9"
4120	20'	15 7/8"	13 7/8"	38.6	22' 8"
4124	24'	15 7/8"	13 7/8"	44.5	26' 7"



## Aluminum D Rung



## Non-Marring End Cap



## Slip Resistant Shoe



MODEL	LADDER SIZE	OUTSIDE WIDTH	INSIDE WIDTH	APPROX. WEIGHT (LBS)	MAX. REACH
3108D	8'	17 13/16"	15 9/16"	13.5	11' 1"
3110D	10'	17 13/16"	15 9/16"	17.1	13'
3112D	12'	17 13/16"	15 9/16"	20.1	15' 0"
3114D	14'	18"	15 3/8"	25.6	16' 11"
3116D	16'	18"	15 3/8"	29.3	18' 10"
3118D	18'	18"	15 3/8"	36.7	20' 8"
3120D	20'	18"	15 3/8"	40.8	22' 8"



ASSEMBLED IN  
ASSEMBLÉ AU  
CANADA

# ALUMINUM EXTENSION




## Box Section Design



## Side Mounted Pulley



## D Rung



MODEL	LADDER SIZE	BASE SECTION		FLY SECTION		APPROX. WEIGHT LBS	MAX. REACH
		MAX. OPEN LENGTH	OUTSIDE WIDTH	INSIDE WIDTH	OUTSIDE WIDTH		
4216D	16'	13'	17 5/8"	15 3/16"	14 5/8"	12 7/8"	30.1
4220D	20'	17'	17 5/8"	15 3/16"	14 5/8"	12 7/8"	38.5
4224D	24'	21'	17 5/8"	15 3/16"	14 5/8"	12 7/8"	44.2
4228D	28'	25'	17 5/8"	15 3/16"	14 5/8"	12 7/8"	55.3
4232D	32'	29'	18 3/8"	16 3/8"	15 7/8"	13 7/8"	63.2
4236D	36'	32'	18 3/8"	16 3/8"	15 7/8"	13 7/8"	74.0
4240D	40'	35'	18 3/8"	16 3/8"	15 7/8"	13 7/8"	83.2
4244D	44'	39'	18 3/8"	16 3/8"	15 7/8"	13 7/8"	90.9

4200D



## D Rung



## Max Lock



## Swivel Safety Shoe



MAX LOCK™

THE  
STRONGEST,  
TOUGHEST,  
LIGHTEST  
RUNG LOCK  
EVER.

3200D

MODEL	LADDER SIZE	BASE SECTION		FLY SECTION		APPROX. WEIGHT LBS	MAX. REACH
		MAX. OPEN LENGTH	OUTSIDE WIDTH	INSIDE WIDTH	OUTSIDE WIDTH		
3216D	16'	13'	17 13/16"	15 9/16"	15 3/8"	13 1/8"	28.2
3220D	20'	17'	17 13/16"	15 9/16"	15 3/8"	13 1/8"	34.8
3224D	24'	21'	17 13/16"	15 9/16"	15 3/8"	13 1/8"	40.9
3228D	28'	25'	18 1/16"	15 3/8"	15 15/16"	13 5/16"	54.0
3232D	32'	29'	18 1/16"	15 3/8"	15 15/16"	13 5/16"	60.8
3236D	36'	32'	18 1/16"	15 3/8"	15 15/16"	13 5/16"	73.9
3240D	40'	35'	18 1/16"	15 3/8"	15 15/16"	13 5/16"	81.0



## Aluminum Pulley



## Rung Lock



## Slip Resistant Shoe



2200

MODEL	LADDER SIZE	BASE SECTION		FLY SECTION		APPROX. WEIGHT LBS	MAX. REACH
		MAX. OPEN LENGTH	OUTSIDE WIDTH	INSIDE WIDTH	OUTSIDE WIDTH		
2216	16'	13'	16 3/8"	14 1/2"	15 3/16"	13 5/16"	19.4
2220	20'	17'	16 3/8"	14 1/2"	15 3/16"	13 5/16"	26.4
2224	24'	21'	16 3/8"	14 1/2"	15 3/16"	13 5/16"	32.4
2228	28'	25'	16 3/8"	14 5/8"	15 1/16"	13 5/16"	39.8
2232	32'	29'	17 1/8"	15 1/4"	16 1/16"	14 3/16"	55.1
2240	40'	35'	17 1/8"	15 1/4"	16 3/16"	14 5/16"	76.8



3 in 1

Step



Stairway



Extension



MODEL	STEP SIZE	EXTENSION SIZE	MAX. EXTENSION OPEN LENGTH	APPROX. WEIGHT (LBS)	MAX. REACH STEP	MAX. REACH EXTENSION
2706	6'	12'	9'	22.8	10' 5"	14' 12"
2707	7'	14'	11'	25.7	11' 4"	16' 11"
2708	8'	16'	13'	28.5	12' 3"	18' 10"



## CROSSXSTEP



Top



Lock



Shox/Boot



MODEL	LADDER SIZE	BOTTOM WIDTH (IN)	APPROX. SPREAD (IN)	APPROX. WEIGHT (LBS)	APPROX. CUBES (FT)	SHELFLADDER		STEPLADDER	
						HIGHEST STANDING LEVEL (IN)	MAX. REACH	HIGHEST STANDING LEVEL (IN)	MAX. REACH
FXS6904	4'	20 1/4"	24	15.2	4	11"	7' 6"	1' 11"	8' 6"
FXS6906	6'	23 1/4"	36	21.3	6.8	3' 10"	10' 5"	3' 10"	10' 5"
FXS6908	8'	26 1/4"	48	28.5	10.1	4' 9"	11' 4"	5' 8"	12' 3"
FXS6910	10'	29 1/4"	60	40.3	14	6' 8"	13' 3"	7' 7"	14' 2"
FXS6912	12'	32 3/8"	71	48.7	18.5	8' 7"	15' 2"	9' 6"	16' 1"

FXS6900

ASSEMBLED IN  
ASSEMBLÉ AU  
CANADA

# CONNECT

WITH FEATHERLITE AT



Check out the personal side of Featherlite Ladders.



Visit the Featherlite Ladders Website for up to date product info and where to buy.



Connect with the Featherlite Ladders community.



Engage with the Professional side of Featherlite Ladders.

## TERMS AND CONDITIONS

Louisville Ladder, Corp. is herein referred to as the "Seller" and the customer or person or entity purchasing goods ("Goods") from Seller is referred to as the "Buyer". These Terms and Conditions, any quotation or acknowledgment from Seller relevant to the sale of the Goods and all documents incorporated by specific reference therein, constitute the complete and exclusive statement of the terms of the agreement governing the sale of Goods by Seller to Buyer. Any other language proposed by Buyer, including Buyer's Purchase Order language shall not control over these Terms. Buyer's acceptance of the Goods will manifest Buyer's assent to these Terms and Conditions.

1. PRICES: All prices are exclusive of taxes, transportation and insurance, which are to be borne by Buyer.

2. TAXES: Any tax or governmental charge affecting Seller's costs of production, sale, or delivery shall be added to the price.

3. TERMS OF PAYMENT: Unless otherwise specified by Seller, terms are 1% ten (10), net thirty (30) days from date of Seller's invoice in U.S. currency. Seller shall have the right, among other remedies, either to terminate this and/or other agreements with Buyer in the event Buyer fails to make any payment when due. Buyer shall be liable for all expenses, including attorneys' fees, relating to the collection of past due amounts. Should Buyer's financial responsibility become unsatisfactory to Seller, cash payments or security satisfactory to Seller may be required by Seller for future deliveries and for the Goods theretofore delivered.

4. SHIPMENT AND DELIVERY: Deliveries are made F.O.B. Seller's shipping point. Risk of loss or damage and responsibility shall pass from Seller to Buyer upon delivery. Any claims for shortages or damages suffered in transit shall be submitted by the Buyer directly to the carrier. While Seller will use all reasonable commercial efforts to maintain the delivery date(s) acknowledged or quoted by Seller, all shipping dates are approximate and not guaranteed. Seller reserves the right to make partial shipments. Seller, at its option, shall not be bound to tender delivery of any Goods for which Buyer has not provided shipping instructions. If the shipment of the Goods is postponed or delayed by Buyer for any reason, Buyer agrees to reimburse Seller for any and all storage costs and other additional expenses resulting therefrom.

5. LIMITED WARRANTY: Subject to the limitations of Section 7, Seller warrants that the Goods manufactured by Seller will be free from defects in material and under normal use and regular service and maintenance for a period of one year from the date of shipment of the Goods by Seller, unless otherwise specified by Seller in writing. THIS IS THE SOLE AND EXCLUSIVE WARRANTY GIVEN BY SELLER WITH RESPECT TO THE GOODS AND IS IN LIEU OF AND EXCLUDES ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, ARISING BY OPERATION OF LAW OR OTHERWISE, INCLUDING WITHOUT LIMITATION, MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE WHETHER OR NOT THE PURPOSE OR USE HAS BEEN DISCLOSED TO SELLER IN SPECIFICATIONS, DRAWINGS OR OTHERWISE, AND WHETHER OR NOT SELLER'S PRODUCTS ARE SPECIFICALLY DESIGNED AND/OR MANUFACTURED BY SELLER FOR BUYER'S USE OR PURPOSE. This warranty does not extend to any losses or damages due to misuse, accident, abuse, neglect, normal wear and tear, Buyer's negligence, unauthorized modification or alteration, use beyond rated capacity, or improper installation, maintenance or application. To the extent that Seller has relied upon any specifications, information, representation of operating conditions or other data supplied by Buyer or its agents to Seller in the selection or design of the Goods and the preparation of Seller's quotation, and in the event that actual operating conditions or other conditions differ from those represented by Buyer and relied upon by Seller, any warranties or other provisions contained herein which are affected by such conditions shall be null and void. If within thirty (30) days after Buyer's discovery of any warranty defects within the warranty period, Buyer notifies Seller thereof in writing, Seller shall, at its option, repair, correct or replace F.O.B. point of manufacture, that portion of the Goods found by Seller to be defective. Failure by Buyer to give such written notice within the applicable time period shall be deemed an absolute and unconditional waiver of Buyer's claim for such defects. Goods repaired or replaced during the warranty period shall be covered by the foregoing warranty for the remainder of the original warranty period or ninety (90) days, whichever is longer. Buyer assumes all other responsibility for any loss, damage, or injury to persons or property arising out of, connected with, or resulting from the use of Goods, either alone or in combination with other products/components.

6. LIMITATION OF REMEDY AND LIABILITY: THE SOLE AND EXCLUSIVE REMEDY FOR BREACH OF ANY WARRANTY HEREUNDER (OTHER THAN THE WARRANTY PROVIDED UNDER SECTION 7) SHALL BE LIMITED, AT SELLER'S OPTION, TO REPAIR, CORRECTION OR REPLACEMENT. UNDER SECTION 5, SELLER SHALL NOT BE LIABLE FOR DAMAGES CAUSED BY DELAY IN PERFORMANCE AND IN NO EVENT, REGARDLESS OF THE FORM OF THE CLAIM OR CAUSE OF ACTION (WHETHER BASED IN CONTRACT, INFRINGEMENT, NEGLIGENCE, STRICT LIABILITY, OTHER TORT OR OTHERWISE), SHALL SELLER'S LIABILITY TO BUYER AND/OR ITS CUSTOMERS EXCEED THE PRICE

PAID BY BUYER FOR THE SPECIFIC GOODS PROVIDED BY SELLER GIVING RISE TO THE CLAIM OR CAUSE OF ACTION. BUYER AGREES THAT IN NO EVENT SHALL SELLER'S LIABILITY TO BUYER AND/OR ITS CUSTOMERS EXTEND TO INCLUDE INCIDENTAL, CONSEQUENTIAL OR PUNITIVE DAMAGES. The term "consequential damages" shall include, but not be limited to, loss of anticipated profits, business interruption, loss of use or revenue, cost of capital or loss or damage to property or equipment. It is expressly understood that any technical advice furnished by Seller with respect to the use of the Goods is given without charge, and Seller assumes no obligation or liability for the advice given, or results obtained, all such advice being given and accepted at Buyer's risk.

7. PATENTS AND COPYRIGHTS: Subject to the limitations of the second paragraph of Section 6, Seller warrants that the Goods sold, except as are made specifically for Buyer according to Buyer's specifications, do not infringe any valid U.S. patent or copyright in existence as of the date of shipment. This warranty is given upon the condition that Buyer promptly notify Seller of any claim or suit involving Buyer in which such infringement is alleged, and, that Buyer cooperate fully with Seller and permit Seller to control completely the defense, settlement or compromise of any such allegation of infringement. Seller's warranty as to use only applies to infringements arising solely out of the inherent operation of such Goods. In the event such Goods are held to infringe such a U.S. patent or copyright in such suit, and the use of such Goods is enjoined, or in the case of a compromise or settlement by Seller, Seller shall have the right, at its option and expense, to procure for Buyer the right to continue using such Goods, or replace them with non-infringing Goods, or modify same to become non-infringing, or grant Buyer a credit for the depreciated value of such Goods and accept return of them.

8. EXCUSE OF PERFORMANCE: Seller shall not be liable for delays in performance or for non-performance due to acts of God; acts of Buyer; war; fire; flood; weather; sabotage; strikes, or labor or civil disturbances; governmental requests, restrictions, laws, regulations, orders or actions; unavailability of or delays in transportation; default of suppliers; or unforeseen circumstances of any events or causes beyond Seller's reasonable control. Deliveries or other performance may be suspended for an appropriate period of time or canceled by Seller upon notice to Buyer in the event of any of the foregoing, but the balance of the agreement shall otherwise remain unaffected as a result of the foregoing. If Seller determines that its ability to supply the total demand for the Goods, or to obtain material used directly or indirectly in the manufacture of the Goods, is hindered, limited or made impracticable due to causes set forth in the preceding paragraph, Seller may allocate its available supply of the Goods or such material (without obligation to acquire other supplies

of any such Goods or material) among its purchasers on such basis as Seller determines to be equitable without liability for any failure of performance which may result therefrom. Seller reserves the right to change designs and specifications for the Goods without prior notice to Buyer, except with respect to Goods being made-to-order for Buyer.

9. ASSIGNMENT: Buyer shall not assign its rights or delegate its duties hereunder or any interest therein or any rights hereunder without the prior written consent of the Seller, and any such assignment, without such consent, shall be void.

10. GENERAL PROVISIONS: These terms and conditions supersede all other communications, negotiations and prior oral or written statements regarding the subject matter of these terms and conditions. No change, modification, rescission, discharge, abandonment, or waiver of these terms and conditions shall be binding upon the Seller unless made in writing and signed on its behalf by a duly authorized representative of the Seller. No conditions, usage or trade, course of dealing or performance, understanding or agreement purporting to modify, vary, explain, or supplement these terms and conditions shall be binding unless hereafter made in writing and signed by the party to be bound, and no modification shall be affected by the Seller's receipt, acknowledgment, or acceptance of purchase orders, shipping instruction forms, or other documentation containing terms at variance with or in addition to those set forth herein. No waiver by either party with respect to any breach or default or of any right or remedy and no course of dealing, shall be deemed to constitute a continuing waiver of any other breach or default or of any other right or remedy, unless such waiver be expressed in writing and signed by the party to be bound. All typographical or clerical errors made by Seller in any quotation, acknowledgment or publication are subject to correction. The validity, performance, and all other matters relating to the interpretation and effect of this agreement shall be governed by the law of the state of Kentucky. Buyer and Seller agree that the proper venue for all actions arising in connection herewith shall be only in the State where the Goods involved in such actions were manufactured and the parties agree to submit to such jurisdiction.



## FEATHERLITE

### CANADIAN HEAD OFFICE

100 ENGELHARD DRIVE  
AURORA, ON, L4G 3V2

PHONE	905-727-0031
TOLL FREE	800-867-5233
FAX	905-727-7271

## LOCATIONS

### › ONTARIO - HEAD OFFICE

100 Engelhard Drive,  
Aurora, ON, L4G 3V2  
PHONE: (905) 727-0031

### › ONTARIO - WAREHOUSE

100 Engelhard Drive,  
Aurora, ON, L4G 3V2  
PHONE: (905) 727-0031

### › QUEBEC

2001 Francis Hughes  
Laval, QC H7S 2G2  
PHONE: (450) 668-4610  
FAX: (450) 668-4611

### › BRITISH COLUMBIA

17260 Heather Drive,  
Unit 202, Surrey, BC, V3S 0B4  
PHONE: (604) 940-2972  
FAX: (604) 940-2973

# FEATHERLITE

FULL LINE CATALOG 2026

## CANADIAN HEAD OFFICE

100 ENGELHARD DRIVE  
AURORA, ON, L4G 3V2

**PHONE** 905-727-0031  
**TOLL FREE** 800-867-5233  
**FAX** 905-727-7271